



MONSTER TAPE

High Strength Water Resistant Tape

Technical Data Sheet



TIGRIS TAPE RANGE

Description:

A self-adhesive, all purpose, heavy duty tape with high tack for binding, fixing, sealing, repairing, joining, protecting, marking and much more.

Features & Benefits:

- ♦ *High adhesion strength.*
- ♦ *Water resistant.*
- ♦ *Easy tear.*
- ♦ *Heavy duty.*
- ♦ *Can be applied to damp surfaces.*

Uses

Rubber based adhesive provides long lasting adhesion on most substrates, and will adhere to rough surfaces.

Can be applied to wet and damp surfaces. Temporary (max. 5 hours) leak repair and water immersion. Will withstand short term water exposure e.g. rain showers.

Do not use on dusty or oily surfaces. It is the users responsibility to determine suitability of use.

Application

1. Ensure surfaces are clean, free from dust and relatively dry.
2. Remove outer packaging from roll of tape.
3. Peel required amount of tape from roll, pressing firmly into place whilst unrolling.
4. Cut with a knife or tear when finished.

Size

48mm x 11m rolls.

Colour

Black.

Shelf Life

Maximum 5 years from date of manufacture.

Storage Conditions

Store in original, unopened packs in dry conditions, out of direct sunlight between +5°C and +25°C.



Disposal Of Containers

Do not leave unused product or discarded materials on site where it could be harmful to children, animals or the environment. Remove to a central disposal point in accordance with local regulations.

Health & Safety

This product will cause no major hazard or problem to the users health. Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Backing	PE laminated synthetic cloth
Adhesive	Natural rubber
Density	ca. 454g/m ²
Thickness	420 microns +/- 10%
Tensile Strength	>180 N
Adhesion to Steel Plate	>5.5N/cm
Temperature Resistance	ca. 2 hours @ +80°C
Commodity Code	3919909090



Product / Order Details

Code	Colour	Size	Barcode	UFI
BDWPT48	Black	48mm x 11M	5056437400222	-

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Part of the Bond It Tape Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.
Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com
EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411
Website: www.bonditgroup.com



Version 4: Updated 10/09/24
 Supersedes: V3 15/10/21

bond it

An **ASTRAL** Limited Company