

TWO-PART WOOD FILLER

Tough Durable Polyester Resin Filler for Permanently Repairing Wood

Technical Data Sheet



DECORATORS RANGE

Description:

A tough, durable, two part wood filler based on polyester resin. Long lasting repair for all wood types.

Features & Benefits:

- ♦ Can be stained, painted, varnished or dyed once cured.
- ♦ Chemical curing system - sets hard in 30 minutes to any depth.
- ♦ Sandable in 30 minutes.
- ♦ High strength; can be drilled, nailed, planed and carved once dry.
- ♦ Good movement capabilities to flex with wood.
- ♦ No shrinking or cracking.
- ♦ Waterproof.
- ♦ Suitable for internal and external application.

Uses

General wood filling of windowsills, frames, banisters, MDF and laminates, etc. Repairing wood damaged by wet rot in both internal and external locations. Repair damage and chips to parquet or laminate flooring, wooden furniture, etc.

Limitations

Do not attempt to push mixture back into pack once mixed. Avoid contact with eyes and skin. Always test a small inconspicuous area for colour matching purposes. Throw away any unused mixed material after 10 minutes.

Preparation

Remove any contamination that may affect adhesion. Any rotten wood should be totally removed.

If you intend to overstain the repair, choose the filler colour closest to the wood you are filling, not the stain you intend to use. Always check the stain on a small area as the filler may absorb the stain at a different rate to the wood.

Application

Mix a golf ball volume of filler (approx. 38mm diameter and a 38mm strip of hardener into a homogeneous paste with the spatula provided. Press firmly into the surface to be repaired, leaving it slightly proud. Leave to dry for about 30 minutes until hard before finishing (sanding and or painting/staining).

Cleaning Of Tools

Clean tools with warm, soapy water



Size

275ml metal tins.

Colour

Available in 5 colours pine, white, light oak, dark oak.

Shelf Life

24 months from date of manufacture when stored in original sealed containers. Protect from frost.

Storage Conditions

Store upright in cool, dry conditions in original sealed container between +10 and +20°C. Keep away from direct sunlight and sources of ignition. Keep containers sealed.

Disposal Of Containers

Do not leave empty containers where residue could be harmful to children, animals or the environment. Replace lids and remove any containers or used material to a central disposal point in accordance with local regulations.

Health & Safety

Please refer to separate safety data sheet (SDS) for full handling, use and storage instructions. Keep out of reach of children. It is the user's responsibility to determine suitability for use. If in doubt, contact our Technical Department for advice.

Note: this information is for general guidance only, since site conditions and labour are beyond our control.

Specification Summary

Base	2-part system: Polyester resin with Benzyl Peroxide hardener
Flammability	Heating may cause fire
Consistency	Thick paste
Open Time	10 minutes maximum
Shrinkage	Nil at all depth
Working Temperature	+5°C to +30°C. (Optimum 20°C).
Temperature Resistance	-20°C to +100°C
Density	ca. 1.10g/cm ³
Commodity Code	3214101000



Product / Order Details

Code	Colour	Size	Barcode	UFI
BDWF2PN	Pine	275ml	5056437400253	2060-A00D-800A-Q34V
BDWF2WH	White	275ml	5056437400246	2060-A00D-800A-Q34V
BDWF2LO	Light oak	275ml	5056437400260	2060-A00D-800A-Q34V
BDWF2TK	Teak	275ml	5056437400543	2060-A00D-800A-Q34V
BDWF2DO	Dark Oak	275ml	5056437400536	2060-A00D-800A-Q34V



Part of the Bond It Decorating Sundries Range

Head Office: Unit H4, Premier Way, Lowfields Business Park, Elland, West Yorkshire. HX5 9HF.

Telephone: +44 (0)1422 315300 **Email:** salesuk@bonditgroup.com

EU Office: SISL (Bond It) Ireland Limited, 70 Sir John Rogerson's Quay, Dublin 2. **Tel:** +353 1 960 9411

Website: www.bonditgroup.com

Note: The data presented in this leaflet is in accordance with the present state of our knowledge, but does not absolve the user from carefully checking all supplies immediately on receipt. We reserve the right to alter product constants within the scope of technical progress or new developments. The recommendations made in this leaflet should be checked by preliminary trials because of conditions during processing over which we have no control, especially where other companies raw materials are also being used. The recommendations do not absolve the user from the obligation of investigating the possibility of infringement of third parties rights and, if necessary clarifying the position. Recommendations for use do not constitute a warranty, either expressed or implied, of the fitness or suitability of the products for a particular purpose.



Version 5: Updated 09/09/24
Supersedes: V4 15/02/21

bond it

An **ASTRAL** Limited Company